

Mediatrix® 4400 Series

The Mediatrix 4400 Digital Gateways allow enterprises to lower communications costs over any IP link. The units feature ISDN BRI interfaces. They provide an ideal solution for enterprise voice applications or for connecting to a service provider's broadband access.



Key Benefits

- 1, 2 or 4 ISDN BRI interface ports
- Up to 8 simultaneous calls
- Secured SIP signalling and media transmission
- User programmable call handling
- Deployable in SIP VoIP networks
- HTTP, SNMP, FTP and TFTP for configuration and management
- Fax over IP support, including T.38
- Multiple codec support
- Multiple LEDs for status indication at a glance

Mediatrix 4400 Overview

Designed specifically for enterprise applications, the Mediatrix 4400 digital gateways make use of existing broadband access equipment to connect to any standards based VoIP network.

The Mediatrix 4400 digital gateways meet the requirements of enterprises that want to connect their ISDN equipment, such as PBXs, through a BRI interface to an IP network or as a gateway to the PSTN.

Mediatrix 4400 digital gateways provide transparent ISDN port extensions over an IP network. The remote ISDN terminals can be managed centrally and benefit from PBX services such as calling groups and voice mail.

The Mediatrix 4400 offers security features such as TLS, SRTP, certificates management, and HTTPS designed to bring enhanced security for the network management, SIP signalling and media transmission aspects.

Applications

The Mediatrix 4400 digital VoIP gateways allow any office to use an existing IP network for lower-cost voice communications.

The Mediatrix units link any standard ISDN BRI connection to the IP network and deliver the clarity of toll quality voice for a comprehensive VoIP solution.

T.38 FoIP, fax bypass, and modem bypass capabilities ensure that the Mediatrix 4400 digital gateways seamlessly transport voice and data services. The Mediatrix 4400 digital gateways offer flexibility and scalability for VoIP network integration and low bandwidth voice.

With configurable NT/TE BRI ports, call-switching and user programmable call routing (including caller/called ID), Mediatrix 4400 digital gateways integrate smoothly into existing PBX and PSTN networks.



denk-stein:net

MEASUREMENT TECHNOLOGY

Franklinstr.13a ■ D-10587 Berlin ■ Germany

+49-(0)30-398981-0 +49-(0)30-398981-39

sales@denk-stein.com www.denk-stein.com

Vertrieb & Systemintegrator für Carrier + Corporate Networks

Media5 Sales Department

Mediatrix 4400 BRI Digital Gateway

- 1 to 4 ISDN BRI ports software configurable as NT or TE
 - 4401 = 1 BRI port
 - 4402 = 2 BRI ports
 - 4404 = 4 BRI ports
- Up to 8 simultaneous calls
- Configurable point-to-point, point-to-multipoint and connector pinout
- Optional cut-through relay for emergency operation (bypass connection) between port 1 and 2.
- Optional Power Over Ethernet
- Optional Power Feeding Module for BRI phones

Technical Specifications

Voice Processing

- Vocoders: G.711 (A-law, μ -law), G.723.1, G.726, G.729a/b
- G.168 echo cancellation
- DTMF detection and generation
- Carrier tone detection and generation
- Silence detection / suppression and Comfort Noise Generation level software adjustable
- Configurable dejitter buffer
- Configurable tones (dial, ringing, busy)
- Configurable transmit packet length
- RTP/RTCP - RFC 1889, RFC 1890, RFC 2833, RFC 3389

Enhanced Security

- HTTPS, for the exchange of Configuration File.
- SRTP with MIKEY as key selection method.
 - Supported Cypher
 - AES – 128 bits
- MIKEY protocol using pre-shared keys (RFC 3830 and 4567) for negotiating SRTP keys.
- Certificate management.
- TLS transport method.
 - Supported Key Exchange Mechanism:
 - RSA
 - Diffie-Hellman
 - Supported Cyphers (minimum):
 - AES (128 and 256 bits)
 - 3DES (168 bits)

Fax and Modem Support

- Fax over IP
- T.38 Fax relay (9.6 k, 14.4 k)
- G.711 Fax and Modem Bypass
- Clear channel (G.711) or T.38

IP Telephony Protocol

- SIP

Voice Signalling

- Euro ISDN EDSS-1 / ETSI PRI/NET5
- ETS 300 012-1 (ITU-T I.430)
- ETS 300 402-2 (ITU-T Q.921)
- ETS 300 403-1/2 (ITU-T Q.931)
- ETS 300 102-2 (ITU-T Q.931)
- ETS 300 402-1 (ITU-T Q.921)
- ETS 300 403-2 (ITU-T Q.931)
- ETS 300 102-1 (ITU-T Q.931)
- ISDN speech, audio and data (Fax Gr 4, UDI 64, RDI 64)

Voice Routing

- Local switching
- Interface hunt groups
- Routing Criteria
 - Interface
 - Calling/called party number
 - Time of day, day of week, date
 - ISDN bearer capability
- Number manipulation functions
 - Replace numbers
 - Add/remove digits
 - Multiple remote gateways
 - PLAR

QoS

- TOS/DiffServ
- IEEE 802.1p/Q

Management

- Web-based GUI
- TFTP, FTP, HTTP configuration up- and download (Auto-provisioning)
- TFTP, FTP, HTTP firmware upgrade
- SNMPv1, v2 and v3 agent (MIB II and private MIB)

WAN Connection

- 1 x 10/100 BaseT Ethernet RJ-45 connector

Operating Environment

- Operating temperature: 0°C to 40°C
- Storage temperature: -20°C to +70°C
- Humidity: up to 85 %, non-condensing

Power Supply

- External 12 Vdc power supply (wall plug or desktop, based on country/area model).

Mechanical

- Desk mount (horizontal/vertical) or Wall mount

Dimensions

- Height: 4.9 cm (1.9 in.) approx.
- Width: 22 cm (8.7 in.) approx.
- Depth: 17.6 cm (6.9 in.) approx.
- Weight: 545 g (0.75 lb.) approx.